

100% Environmental Friendly since in its processes, it is used neither generated no polluting type of dissolvent nor paticles



Best quality in Mill Finish
Innovation Pre-Treatment Chemical

3. The highest quality in Powder Coating

Longer **Sustainability** in the time

- Powder coating superior of 60μ , guaranteeing optimal specificationses of the final product, diminishing its aging without any loss of the gloss and the brightness throught the time.
- Homogeneous Powder Coating.
- High adhesion of the powder coating to the raw material.
- Greater anticorrosive protection incorporating with an innovating chemical pre-processing.
- Superior resistance to the abrasion and the environmental erosion, mainly by its thickness of painting superior to 60μ .

High Performance of Manipulation

ApliMAX`s treatment, guarantee an extraordinary mechanical manipulation mainly by its high flexibility, verified by the main norms of the market.

Característics		Normatives		Specification	
Adhesion	EN	ISO 2409 / ECCA	T-6	GT O	
Impact	EN	ISO 6272 / ECCA	T-5	3 Nm	
Bending*	EN	I ISO 1519 / ECCA	T-7	ОТ	
		*[*Depending of the thickness		

ApliMAX, due to its coating superior to **60**µ, in front of other products of the market, offers a **greater resistance** to the inadequate manipulation of the product, such as scratche or, impact, among others, own of the assembly...



- Exterior: Façade, closing, covers, panels sandwich, doors or strutural, corporative image, industrial rotulation, windows farme complements (aesthetics of profiles) etc.
- Interior: Exhibitors, stands, electric home appliances, silkscreen printing, celling façade, furniture and decoration, visual contact, industrial applications, ventilation façade.